# IL BETAFENCE

# CreaZen<sup>®</sup> swing gate

### **Product detail**



## Gates

The CreaZen gates are available as single and double swing gates.

The CreaZen infill fits harmoniously with the CreaZen raling system.

#### **BENEFITS**

- The design is in perfect harmony with the CreaZen panels.
- Rigid and qualitative construction.
- With aesthetic and high quality stainless steel accessories.
- Universal 180° opening

#### Frame

The gate frame consists of steel tubes, 60x40 mm, which are welded at both sides of the CreaZen panel. This results in a very rigid construction. The complete frame is hot dip galvanized and PES coated.

#### Posts

Each gate has got 2 gate posts, which are included in the packaging. Standard the posts are to be put into concrete. Posts with welded floor plates are available on request.

Post section:

For single gates: 100x100x3 mm For double gates: 120x120x3 mm

The gate posts are hot dip galvanized and PES coated and have got a plastic cap. The posts are standard fore-

seen with inserts to enable fixation of CreaZen panels.

#### Accessories

A box containing all accessories is included with each gate:

- built-in lock with stainless steel cover plates
- symmetrical European cylinder, with 3 keys
- strong hinges, fully reversible left/right and allowing 180° opening of the gate wing.
- · decorative handles
- gate catcher installed on the post or wing)

#### Coating technique

Both gate wing(s) and posts are hot dip galvanized and PES coated.



#### Colours

Anthracite RAL 7016, other colours are available on request.

ASSORTMENT CREAZEN SWING GATES					
Width mm	Height mm	Wing width mm	Post length (installation in concrete) mm	Distance between posts (centre/centre) mm	Overall width mm
Single swing gates					
1200	1000	1200	1600	1340	1440
	1200		1800		
	1500		2100		
	1700		2300		
	2000		2600		
Double swing gates					
4000	1000	2x2000	1600	4180	4300
	1200		1800		
	1500		2100		
	1700		2300		
	2000		2600		

## **Applications**







